

1800KG Auto Slide Sliding Gate Opener Automatic w 4m Rail

RRP: \$1,379.95

With its ultra-smooth yet ultra-powerful operation, the Sliding Gate Opener has the smart features you're looking for — and all at an ultra-affordable price.

With a huge output power of 550W, this diecast aluminum alloy motor can power a gate weighing up to 1,800kg. Quality construction includes an alloy baseplate and a 4m steel-reinforced nylon gear rack. This rack not only ensures silent operation, but it also ensures a long life for your opener.

Several safety features are included for your peace of mind. There's a stop and auto-reverse mode for obstructions, and the sensitivity of this mode is customisable. There's a manual release for any power outages, overload protection, and an auto close function with an adjustable delay time. There's even an auto warm-up feature at freezing temperatures to ensure you're never "stuck out in the cold." The opener will operate at temperatures approaching -22°C!

You'll receive 3 remote controls with your purchase. Full hardware and easy-to-follow DIY instructions are also included.


For a smooth and silent sliding gate for home or business, we've got your answer. Purchase the HUH-PE Sliding Gate Opener today.

Features:

- Powerful die-cast aluminium alloy motor
- Soft, smooth and silent openings and closings
- Alloy baseplate
- Steel gear
- 4m Rail - steel reinforced nylon gear rack
- Stop and reverse mode in case of obstruction (customisable sensitivity)
- Auto-close function is fully adjustable
- Auto warm-up for low temperatures
- Emergency release keys for manual operation in case of power failure
- 3 x remote controls (433.92 Mhz); operation at up to 30m
- 4-button operation: close, open, stop and pedestrian open
- Electromagnetical limit switch
- Full user manual and all installation hardware included
- Gate is NOT included

Specifications:

- Voltage: 240V AC
- Output power: 550W
- Current: 2 amps
- Overload protection
- Travel speed: 12m/min
- Maximum weight of gate: 1800kg



- Operating temperature: -22°C to +55°C
- CE/EMC approval model

Optional Extras Available For Purchase:

- Additional 4m Length of Nylon Gear Rack
- 4m U-Groove Galvanised Ground Track
- Additional Remote Control/s
- Wireless Entry Keypad

Item Code: HUH-2A

Note: Assembly must be done by a licensed Electrician